




KERUING PANEL N°51 RHOMBUS 1800X1800MM

- Keruing Tropical Hardwood
- Durability class 3
- FSC 100% certified
- High-end assembly, rhombus profile
- Provides you with privacy and security



A ready-to-install panel

Keruing wood, appreciated for its durability and resistance, is ideal for fences. Its dense and hard composition makes it resistant to weather and insects. Its reddish-brown color brings aesthetic warmth and blends perfectly with the garden environment. The strength and beauty of Keruing make it an excellent and durable choice for protecting the exterior.



Environment

LIFETIME	> 20 years
GHG EMISSIONS	0.03 (GES)
RECYCLED MATERIAL	FSC hardwood
END OF LIFE RECYCLABILITY	0 %
CERTIFICATION	FSC®-certified



Characteristics

Specie	Keruing	Class of use	Classe 3
Origin (country)	Indonesia	Density (kg/m3)	790
Main material	Wood		
	Fencing		
Certification	FSC®-certified		
Scientific name	Dipterocarpus spp.		
Botanical family	DIPTEROCARPACAE		
Drying	KD 18 +/-2%		
Durability for fungus	medium durability		
Durability to termites	sensitive		

Logistics Data

REF	EAN CODE	DESIGNATION	WEIGHT (KG)	PACK 1	PACK 2
2284	8720039026827	Keruing Panel n°51 Rhombus 1800x1800mm	27	16	