


Fiberdeck[®]


WE0 ESSENTIAL CLADDING

- ◆ STRIKING NATURAL WOOD LOOK
- ◆ ROT-PROOF AND STAIN-RESISTANT
- ◆ MULTI-CHROMATIC MATT COLOUR



◆ A traditional cladding with beautiful natural looking

WE0 ESSENTIAL cladding renovate your facade with charm and elegance. Installed horizontally or vertically, they can be used to create a warm and traditional style or a contemporary and dynamic look. The boards offer unique performance: rot-proof and highly durable, they are perfectly resistant to stains and UV over time. The 4 colours available in the range are all multichromatic with subtle nuances, giving a highly realistic, natural effect.



◆ Environment

LIFETIME	> 20 years
RECYCLED MATERIAL	wpc
END OF LIFE RECYCLABILITY	95 %
CERTIFICATION	FSC [®] -certified

WEO ESSENTIAL CLADDING

◆ Characteristics

Main material	WPC	Fire classification	Euroclass E
WPC Composition	HDPE : 40% / Wood fibers : 48% / Mineral : 12%	Linear mass (kg/m)	1.64
Certification	FSC®-certified	Anmeldung	MI
Type of surface coextrusion	Co-extrusion	Density (kg/m ³)	1150
Pigmentation	Random pigmentation	Cert. Product class	W9-1
Way of fixation	Vertical or horizontal installation	Certificate group code	FSC TRANSFER
Installation type	To screw		Cladding
Batten spacing (mm)	600		
UV resistant	oui		
Stain resistant	oui		

◆ Logistics Data

REF	EAN CODE	DESIGNATION	WEIGHT (KG)	PACK 1	PACK 2
FD1995	3700421819959	WEO ESSENTIAL - Cladding 15x173mm x 3.9m Teak	6.4	156	
FD1996	3700421819966	WEO ESSENTIAL - Cladding 15x173mm x 3.9m Ipe	6.4	156	
FD1997	3700421819973	WEO ESSENTIAL - Cladding 15x173mm x 3.9m Dark Grey	6.4	156	
FD1998	3700421819980	WEO ESSENTIAL - Cladding 15x173mm x 3.9m Light Grey	6.4	156	


◆ Associated products



ALUMINIUM STARTER PROFILE (2 PCS)



WEO CLADDING - 4X25MM SCREWS (50 PCS)



WEO - ALUMINIUM F PROFILE 35X45 MM



WEO® CLADDING - 4,2X32MM SCREWS (200PCS)